

ORBIS® CCT / DIM

ELEGANT AND MULTIFUNCTIONAL LED WALL/CEILING LUMINAIRES





1
ORBIS
410 22 W 2700-6000 K



2
ORBIS
410 21 W 2700-6000 K



3
ORBIS
310 17 W 2700-6000 K



4
ORBIS
310 16 W 2700-6000 K



Product name	GTIN (EAN)		COLOR	MATERIAL	$t_{[h]}$ ²	W	lm		K	CRI
ORBIS 410 22 W 2700-6000 K	4058075259836	1	White	Aluminum	25000	21.50	1400	A++/A+/A	2700 ... 6000	>80
ORBIS 410 21 W 2700-6000 K	4058075259812	2	White	Aluminum	25000	21.00	1400	A++/A+/A	2700 ... 6000	>80
ORBIS 310 17 W 2700-6000 K	4058075227552	3	White	Aluminum	25000	16.50	1000	A++/A+/A	2700 ... 6000	>80
ORBIS 310 16 W 2700-6000 K	4058075259751	4	White	Aluminum	25000	16.00	1000	A++/A+/A	2700 ... 6000	>80

Product name		IP		$h_{[mm]}$	$\varnothing_{[mm]}$	
ORBIS 410 22 W 2700-6000 K	120	IP20	25000	88.0	410.0	6
ORBIS 410 21 W 2700-6000 K	120	IP20	25000	88.0	410.0	6
ORBIS 310 17 W 2700-6000 K	120	IP20	25000	85.0	310.0	6
ORBIS 310 16 W 2700-6000 K	120	IP20	25000	85.0	310.0	6

¹ The exact terms and conditions can be found at www.ledvance.com/consumer/services/guarantee | ² Average lifetime in hours | ³ Energy efficiency grade of the permanently integrated, non-exchangeable LED modules. Energy efficiency index (EEL) on a scale of A++ (highest efficiency) to E (lowest efficiency).