

ENDURA® STYLE CYLINDER

HIGH-QUALITY LED WALL, CEILING AND PATHWAY LUMINAIRES





1
ENDURA STYLE Cylinder Wall Sensor
6 W ST



2
ENDURA STYLE Cylinder Wall
6 W ST



3
ENDURA STYLE Cylinder
800 6 W ST



4
ENDURA STYLE Cylinder
500 6 W ST



5
ENDURA STYLE Cylinder Ceiling
6 W ST



Product name	GTIN (EAN)	No.	COLOR	MATERIAL	t [h] ²	W	lm	IP ³	K	CRI
ENDURA STYLE Cylinder Wall Sensor 6 W ST	4058075205352	1	Steel	Stainless steel	30000	6.00	360	A++/A+/A	3000	>80
ENDURA STYLE Cylinder Wall 6 W ST	4058075205338	2	Steel	Stainless steel	30000	6.00	360	A++/A+/A	3000	>80
ENDURA STYLE Cylinder 800 6 W ST	4058075205390	3	Steel	Stainless steel	30000	6.00	360	A++/A+/A	3000	>80
ENDURA STYLE Cylinder 500 6 W ST	4058075205376	4	Steel	Stainless steel	30000	6.00	360	A++/A+/A	3000	>80
ENDURA STYLE Cylinder Ceiling 6 W ST	4058075205413	5	Steel	Stainless steel	30000	6.00	360	A++/A+/A	3000	>80

Product name	IP	l [mm]	w [mm]	h [mm]	∅ d [mm]	Weight	
ENDURA STYLE Cylinder Wall Sensor 6 W ST	IP44	15000	150.0	102.0	135.0	6	
ENDURA STYLE Cylinder Wall 6 W ST	IP44	15000	138.0	102.0	135.0	6	
ENDURA STYLE Cylinder 800 6 W ST	IP44	15000	-	-	800.0	102.0	2
ENDURA STYLE Cylinder 500 6 W ST	IP44	15000	-	-	500.0	102.0	2
ENDURA STYLE Cylinder Ceiling 6 W ST	IP44	15000	-	-	87.0	102.0	6

¹ The exact terms and conditions can be found at www.ledvance.com/consumer/services/guarantee | ² Average lifetime in hours | ³ Energy efficiency grade of the permanently integrated, non-exchangeable LED modules. Energy efficiency index (EII) on a scale of A++ (highest efficiency) to E (lowest efficiency).