



Ledinaire panel

RC065B LED34S/840 PSU W60L60 NOC

Power supply unit

The Ledinaire range contains a selection of popular off-the-shelf LED luminaires that comes with the high Philips quality levels at a competitive price. Reliable, energy efficient and affordable – just what you need.

Product data

General information	
Beam angle of light source	– °
Light source color	840 neutral white
Light source replaceable	No
Number of gear units	1 unit
Driver/power unit/transformer	Power supply unit
Driver included	Yes
Optic type	Beam angle 120°
Luminaire light beam spread	120°
Control interface	–
Connection	Push-in connector 2-pole
Cable	–
Protection class IEC	Safety class II
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	CE mark
ENEC mark	ENEC mark
Warranty period	3 years
Constant light output	No
Number of products on MCB of 16 A type B	32

Photobiological risk	Photobiological risk group 0 @ 200mm to EN62471
Photobiological risk specification	0.2 m
EU RoHS compliant	Yes
Service tag	No
Unified glare rating CEN	22

Light technical	
Saturated Red (R9)	<50
Flickering	1
Stroboscopic effect	1.6

Operating and electrical	
Input Voltage	220–240 V
Input Frequency	50 or 60 Hz
Initial CLO power consumption	– W
Average CLO power consumption	– W
Inrush current	16 A
Inrush time	0.18 ms
Power Factor (Min)	0.9

Ledinaire panel

Controls and dimming

Dimmable	No
----------	----

Mechanical and housing

Housing Material	Steel
Reflector material	Acrylate
Optic material	Polystyrene
Optical cover/lens material	Acrylate
Fixation material	-
Optical cover/lens finish	Opal
Overall length	595 mm
Overall width	595 mm
Overall height	34 mm
Color	White RAL 9003
Dimensions (Height x Width x Depth)	34 x 595 x 595 mm (1.3 x 23.4 x 23.4 in)

Approval and application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]

Initial performance (IEC compliant)

Initial luminous flux (system flux)	3400 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	100 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>80
Initial chromaticity	(0.38, 0.38) SDCM≤5
Initial input power	34 W
Power consumption tolerance	+/-10%

Over time performance (IEC compliant)

Control gear failure rate at median useful life	7.5 %
50000 h	

Lumen maintenance at median useful life*	-
35000 h	
Lumen maintenance at median useful life*	70
50000 h	
Lumen maintenance at median useful life*	-
75000 h	
Lumen maintenance at median useful life*	-
100000 h	

Application conditions


Ambient temperature range	-10 to +25 °C
Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	Not applicable

Product data

Full product code	871869979180399
Order product name	RC065B LED34S/840 PSU W60L60 NOC
EAN/UPC - Product	8718699791803
Order code	911401885080
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	911401885080
Net Weight (Piece)	1.900 kg



Dimensional drawing



RC065B LED34S/840 PSU W60L60 NOC

Ledinaire panel

